

## **Terra Systems Core Competencies**

**Customer Driven EVO Formulations** 

Terra Systems, Inc. Research and Treatability Lab is adjacent to manufacturing, which allows us to develop formulation hypothesis, formulate them in the lab and test them in manufacturing.

The development cycle typically begins when a client approaches us with a site where traditional carbon substrates have not worked effectively. This can be due to low pH, high groundwater flow-rates, high concentrations of competing electron acceptors or other technical challenges.

Typically the product development cycle is several years and includes:

- ✓ Literature research
- ✓ Formulation design
- ✓ Laboratory testing of the formulations
- ✓ A treatability study using groundwater and saturated soil from the actual site.
- ✓ A pilot test
- ✓ Modification to the product design and composition based on the lab and field results
- ✓ Full scale implementation.

Examples of successful products developed using these approaches are:

Description	Product	Year
An emulsified oil/zero valent iron		
product with superior injectability	$SRS^{\text{®}}$ - $Z$	2013
for anaerobic and abiotic reduction.		
A large droplet emulsified		
vegetable oil product with a		
proprietary anionic emulsifier for	SRS®-FR	2011
high groundwater flow-rates,		
fractured bedrocks, and permeable		
reactive barriers.		
A small or large droplet emulsified		
vegetable oil product with a	_	
proprietary reductant to accelerate	SRS®-M	2010
metals reduction in a mixed		
chlorinated plume.		
A small droplet emulsified	_	
vegetable oil product with a	SRS®-	2008
nonionic emulsifier for maximum	SD	2008
radius of influence		

In the above cases, a customer approached Terra Systems and challenged us to "develop a better mousetrap" than their current approach for the site.

SRS®-M; Coronado, CA: The site is contaminated with TCE at concentrations of >20 mg/L and >50 mg/L hexavalent chromium. Conventional EVO supported reduction of the hexavalent chromium over 80 days in a microcosm study, but not dechlorination of the TCE after 140 days. In combination with bioaugmentation and a new formulation of SRS® with a proprietary abiotic reductant, the hexavalent chromium was reduced within one day and complete biodegradation of the TCE occurred in 35 days. Field pilot and full scale injections showed that the combination of SRS®-M and bioaugmentation culture could reduce the hexavalent chromium completely and biodegrade the TCE to ethene.

**SRS**<sup>®</sup>-**Z**: The client had chosen a competing product containing zero valent iron (ZVI) and carbon. Customer wanted better injectability and radius of influence (ROI). Injection tests showed that the competing product was difficult to inject and had a ROI of 2.5 feet. Terra Systems developed SRS<sup>®</sup>-Z, which combines 60% SRS<sup>®</sup> and 40% ZVI plus a stabilizer to keep the ZVI in suspension. The SRS<sup>®</sup>-Z was able to achieve a 5 feet ROI and daily inject almost four times the area of the competing product.

SRS®-C; Ensafe Millington, TN: The remediation design was to install a permeable reactive barrier (PRB) with wells on 75 feet spacing's across the downgradient edge of the plume at the property boundary. A combination SRS®-SD and SRS®-FR were used to achieve the maximum radius of influence with the SRS®-SD and the longevity in PRB with the SRS®-FR.

SRS®-FR; High Groundwater Flow Rate Aquifer in Wichita, KS: The site was a highly permeable sandy aquifer with a groundwater flow rate estimated to be 1.9 ft/day. A previous injection of sodium lactate did not result in dechlorination of TCE. Injection of the SRS®-FR and bioaugmentation culture promoted the dechlorination of the TCE to cis-DCE VC, and ethene. The TOC lasted between three to nine months.